

MICRO-LINK

ENHANCED CONTROL INTERFACE




FEATURES

Retains many of the features associated with the OPTI-LINK but in a smaller package.



SPECIFICATION



SPARES

ZE0210I2: Designed specifically for use with the Micro-Link Control Head the Micro-Link receiver offers 6, 5A relay switched outputs plus an auxiliary timed output relay in a compact design. Ideal for operating LED's and associated WOODWAY/WHELEN equipment.



The MICRO-LINK is also ideal for covert installations where the switch panel needs to be hidden from view. Six individual switches and a triple function '999', 'ARRIVAL' & 'RESET' switch provide an enhanced control interface between the driver and the vehicle's emergency equipment. Easy to program by the customer, switches may be set to either latching or momentary.

- Individual switches with clear interchangeable legends. Bespoke legends are available to order.
- Switches 1– 6 are programmable for latching, momentary and mutually exclusive action. '999' & 'ARRIVAL' are installer programmable to operate a pre programmed switch configuration. (No additional equipment is required to program the panel). Programming is protected by a lock code to prevent unauthorised alteration.
- Back lighting on all switches allows switch legends to be easily visible at night. Triple function '999', 'ARRIVAL' & 'RESET' switch changes colour according to the switch function that is active, ('999' blue, 'ARRIVAL' red).
- Auto dim of active switches in low light conditions minimises driver distraction at night.
- Audible and visual warnings confirm to the operator that a switch is active.
- Sleep mode reduces power draw when the vehicle is not in use to prevent battery drain.
- WALK TEST function.
- Screened coiled cable from keypad to keypad interface minimises interference from hand portable radios.

DIMENSIONS

Height: 100mm
Width: 50mm
Depth: 22mm

MODEL NUMBER

MICRO-LINK: MICRO-LINK Switch Panel