

Universeal

flexiGrip™ 300 M+ ISO Cable Seal – Technical Specifications



Physical Strength

Pulling load resistance	11,7 kN
ISO 17712 classification	High Security Seal (suitable for C-TPAT operations) Compliant with new ISO FDIS 17712

Material and Dimensions

Body	Aluminium alloy
L x H x T	26 mm x 26 mm x 7,5 mm
Cable	Non preformed galvanized aircraft cable
Diameter	3,25 mm
Usable length	250 mm
Mechanism	Zinc alloy
Flat spring	Spring steel (Heat treated)
Roller	Steel (Heat treated)

Colours and Printing

Marking zone	26 mm x 19 mm
Printing type	Laser
Printing specifications	First line: Customer ID , Second line: Numbering
Customer ID	Standard: Alphanumeric , Optional: B&W graphic logo
Numbering	Alphanumeric or Barcode
Standard colours (anodized)	Red, Green, Blue, Dark Blue, Yellow, Orange, Grey, Black

Packaging

Bundle	10 pieces sequentially attached with rubber band
Seals per carton	500 pieces in 50 bundles
Carton dimensions	310 mm x 280 mm x 180 mm
Carton weight	Approx. 12,0 kg

Note : Universeal reserves the right to change specifications without prior notice.

January 2011

